

	PAB 20A	PAB 25A		PAB 20A	PAB 25A
Box	2 way, bass-reflex	2 way, bass-reflex	LINE input	2 x RCA	Ø3,5 mm
Pm	120 W	80 W	MIC input	Ø6,3 mm	Ø6,3 mm
Pamp	80 W	60 W	AUX input	-	Ø3,5 mm
Z	4 Ohm	4 Ohm	Stand / Ø	35 mm	35 mm
f	40-20.000 Hz	50-20.000 Hz	Charging time	≈10-12 h	≈4 h
ØWoofer / ØCoil	8" (200 mm) / 1,5" (38 mm) / 30 Oz	10" (250 mm) / 1,5" (38 mm) / 30 Oz	Operation time	≈5-7 h	≈9-10 h
Tweeter	1" (25 mm) compression / 10 Oz	1" (25 mm) compression / 10 Oz	Battery	Lead-acid gel / 12 V / 5000 mAh	Li-ion / 7,4 V / 1800 mAh
File system	FAT16/32-MP3, WMA	FAT16 / 32-MP3	MIC batteries	6LR61 (9V)	2 x AA (1,5 V)
FM range	87,0-108,0 MHz	87,6-108,0 MHz	Remote batteries	CR 2025 (3V)	CR 2025 (3 V)
MIC range	≈10 m / <10mW	≈50 m / <10mW	V / Hz	230 V~ / 50 Hz	230V~ / 50 Hz
MIC frequency	VHF	VHF	Fuse	250 V / 5 A (Ø5 x 20 mm)	
BT version	2.1 / 10 m max.	2.1 / 10 m max.	Ta	0 °C ... +35 °C	0 °C ... +35 °C
BT profiles	A2DP, AVRCP	A2DP, AVRCP	Dimensions / Weight	265 x 390 x 280 mm / 8,1 kg	320 x 460 x 320 mm / 4,8 kg