








<b>AUTO RANGE</b>	<input checked="" type="checkbox"/>
<b>REL. MODE</b>	<input checked="" type="checkbox"/>
<b>VALUE HOLD</b>	<input checked="" type="checkbox"/>
<b>AUTO OFF</b>	<input checked="" type="checkbox"/>
	<input checked="" type="checkbox"/>
<b>-8.8.8.8</b>	<b>max.3999</b>
	<b>max.100 dB</b>
	<b>max.40.000 Lux</b>
<b>°C</b>	<b>0–40 °C</b>
<b>RH%</b>	<b>20–95%</b>
<b>K-type sensor</b>	<b>-20–1000 °C</b>
<b>V<sub>DC</sub></b>	<b>max.1000 V</b>
<b>V<sub>AC</sub></b>	<b>max.750 V</b>
<b>A<sub>DC</sub></b>	<b>max.10 A</b>
<b>A<sub>AC</sub></b>	<b>max.10 A</b>
<b>Hertz</b>	<b>max.200 kHz</b>
<b>Ω</b>	<b>max.99,9 %</b>
<b>Powerfactor</b>	<b>max.40 MΩ</b>
	<b>max.100 μF</b>
	<b>1,5 V/1 mA</b>
	<b>&lt;50 Ω</b>
<b>SAFETY CAT.</b>	<b>CATIII/1000 V,CAT IV/600 V</b>
	<b>4 x AA(1,5 V)</b>
<b>Dimensions</b>	<b>94 mm x 204 mm x 57 mm</b>
<b>Weight</b>	<b>~410 g</b>